


DATA SHEET



S5LPJ2533 Correctal® TL40/3.0

- telecentric lens with
- high NA and c-mount
- with variable iris



outline drawing


DATA SHEET



specifications

article number	S5LPJ2533
design wavelength [nm]	650
magnification (+/-5%)	3.000
working distance [mm] (+/-2%)	100.4
object size [mm]	2.1 x 1.6
at a chip size of [mm]	6.4 x 4.8 (1/2")
distortion [%]	0.1
object size [mm]	2.9 x 2.2
at a chip size of [mm]	8.8 x 6.6 (2/3")
distortion [%]	0.3
object size [mm]	4.2 x 3.2
at a chip size of [mm]	12.8 x 9.6 (1")
distortion [%]	0.5
max. telecentricity error [°]	0.01
numerical aperture	0.12
weight [kg]	0.49
flange back distance [mm]	17.53
accessory	---


Distortion for 650 nm



x = distortion

y = max. field

MTF for various object heights at 650 nm



T. tangential

S. sagittal

graphs and data given by design.

Sill Optics
GmbH & Co. KG
Johann-Höllfritsch-Straße 13
D-90530 Wendelstein

Copyright © Sill Optics GmbH & Co. KG
All rights reserved.
Issue E
Published: 25.08.2017

Tel.: +49 (0) 9129 9023 0
Fax: +49 (0) 9129 9023 23
E-mail: info@silloptics.de
Web: www.silloptics.de

All information contained in this data sheet is for information purposes only and is not binding. The content is subject to change at any time without notification, all information without guarantee. We reserve the right to make constructional changes in the course of product improvement.