

DATA SHEET




S5LPL1223/LED Correctal® TA60/0.16

- telecentric lens
- with c-mount
- with variable iris
- with integrated coaxial illumination

electrical specifications for S5LPLxxx/LED, mechanical interface for S5LPLxxx/CCS and optimum illumination settings for both see [product family data sheet attached](#)



illustration only



outline drawing


DATA SHEET



specifications

article number	SSLPL1223/LED
design wavelength [nm]	623 (+/-11)
magnification (+/-5%)	0.158
working distance [mm] (+/-2%)	190.0
object size [mm]	20.2 x 15.1
at a chip size of [mm]	3.2 x 2.4 (1/4")
distortion [%]	0.09
object size [mm]	30.3 x 22.7
at a chip size of [mm]	4.8 x 3.6 (1/3")
distortion [%]	0.13
object size [mm]	40.5 x 30.3
at a chip size of [mm]	6.4 x 4.8 (1/2")
distortion [%]	0.13
max. telecentricity error [°]	0.05
numerical aperture	0.015
weight [kg]	not yet weighed
flange back distance [mm]	17.53
accessory	S5SET1150, S0SET9125/017, S5SET0020, S5SET2204


Distortion for 586 nm



x = distortion

y = max. field

MTF for various object heights at 586 nm



T. tangential

S. sagittal

graphs and data given by design.

Sill Optics
GmbH & Co. KG
Johann-Höllfritsch-Straße 13
D-90530 Wendelstein

Copyright © Sill Optics GmbH & Co. KG
All rights reserved.
Issue A
Published: 8.07.2019

Tel.: +49 (0) 9129 9023 0
Fax: +49 (0) 9129 9023 23
E-mail: info@silloptics.de
Web: www.silloptics.de

All information contained in this data sheet is for information purposes only and is not binding. The content is subject to change at any time without notification, all information without guarantee. We reserve the right to make constructional changes in the course of product improvement.